Satake's all new full color optcal sorter will provide you the best solution in color soring.

1) New Full Color Sorter

Reliable Japanese designed ejectors and electronics ensure easy and stable operation. The screen can be operated with the same actions as smartphones. Excellent visual screen design provides user-friendly operation.

2) Stable Performance

The machine incorporates advanced software to evaluate the color profile of target defects and automatically creates the optimum sensitivity settings.

LED lighting is utilized for optimum performance and long lifetime to reduce the machine's running cost.

Precise sorting is achieved with a one, two or three stage sorting system. Rejects from the primary-sort can be sorted once or twice more to concentrate the reject.

3) Full Color Camera

The machine is equipped with Japan's latest full color cameras which recognize the target just as the human eye does. Even slight color differences such as light yellow grain can be detected.

No. 764-03 - SEU


Specifications				
Model		EZER		
IVIOC	161	351AIS(2)-T		
Input Capacity	Short-grain rice	0.8~6.4t/h		
	Long-grain rice	0.8~4.3t/h		
Chute Quantity	Primary sorting	2pcs		
	Secondary sorting	1рс		
	Tertiary sorting	-		
Compressor (kW)		15		
Power Supply (V)		Single phase 200 to 240		
Net Weight (kg)		812		

Model		EZER
		701DIS(2)-T
Input Capacity	Short-grain rice	1.2~9.9t/h
	Long-grain rice	1.2~6.6t/h
Chute Quantity	Primary sorting	4pcs
	Secondary sorting	2pc
	Tertiary sorting	1pc
Compressor (kW)		15
Power Supply (V)		Single phase 200 to 240
Net Weight (kg)		812

Model		EZER
		951DIS(2)-1
Input Capacity	Short-grain rice	2.3~19.2t/h
	Long-grain rice	2.3~12.8t/h
Chute Quantity	Primary sorting	6pcs
	Secondary sorting	2рс
	Tertiary sorting	1pc
Compressor (kW)		22
Power Supply (V)		Single phase 200 to 240
Net Weight (kg)		1500

* Nominal capacities based on 3-5% contamination. Sorting performance varies depending on variety, condition of material and initial contaminations.

Dimensions(mm)					
EZER					
351AIS(2)-T	701DIS(2)-T	951DIS(2)-T			
1426	2122	2829			
1719	1719	1719			
1628	1628	1628			
	1426 1719	351AIS(2)-T 701DIS(2)-T 1426 2122 1719 1719			



All copyright and trademark rights of this catalog belong to Satake Co., unless otherwise noted. Unauthorized copying, reprinting, etc. are forbidden. All Satake products are the subject of continuous development and, as a result, their specification may change and differ in detail from those shown

SATAKE CORPORATION

2-30 Saijo Nishihonmachi, Higashi-Hiroshima-shi, Hiroshima-shi, Hiroshima-kan, 739-802, Japan Alpha mighty Dunsan Building, 13F, 229, Daedeck-daero, Seo-gu, 35229 10900 Cash Road, Stafford, Texas, 77477, U.S.A. Rua Xavantes, 155-Pav. 20, Bairro Hors 739-802, Japan URL : www.satake-group.com URL : www.satake-group.com URL : www.satake-usa.com Sataford, Texas, 77477, U.S.A. Altradores, CEP 89203-210, Joinville, Brec	ATAKE EUROPE LTD. forsfield Way, Bredbury Industrial Park, fredbury, Stockport, Cheshire, SK6 2SU, J.K. JRL : www.satake-europe.com
4th Floor, Tower-1, HB Twin Towers, A2, 133,134 Moo 5, Bangkadi, Mueang 888/84 Mahatun Plaza Bid., 8th Floor, Gedung Surabaya Bumi Mandiri, 229 3, 4, Netaji Subhash Place, Wazirpur Pathum Thani, Pathum Thani 12000, Ploenchit Rd., Lumpini, Pathumwan, Lantai 9, Jalan Jenderal Basuki District Centre, New Delhi, 110034, India Thailand Rachmat Nomor 129-137, Unit 905 B, 215	SATAKE MANUFACTURING (SUZHOU) CO., LTD. 229 Jin Feng Road, Suzhou New District, Suzhou, Jiangsu Province, 151529, China JRL : www.satake.cn/
15 Leidand Street Penrith N.S.W (Quality Management Systems) ISO90	SATAKE CORPORATION has obtained ISO9001 and ISO14001 certification. These international standards for management systems ensure Satake will continue to provide high quality products and services.
ISO 14001 Certification system	

Full Color Sorting

EZER 351 / 701 / 951





OPTICAL SORTER

EZER951DIS-T

SATAKE CORPORATION